



Product Code: C1214F

Control, Security, Audio, BMS, 2 Conductor, 14 AWG, BC, PP Ins., PVC, CMR

Product Description

Multi-Conductor, Security, Audio, Control Cable, BMS, 2 Conductor, 14 AWG, Stranded Bare Copper Conductor, Polypropylene Insulation, Shielded, CMR Polyvinyl Chloride Jacket with 210D Nylon Rip Cord

TECHNICAL SPECIFICATION

Suitable Application Control, Audio, Data, Monitoring Building Management System.

Conductor

Element	Conductor(s)
No. of Element	2
Size	14 AWG
Stranding	19x26
Material	Bare Copper

Insulation

Material	PP - Polypropylene
Nominal Thickness (mm)	0.28±0.01
Nominal Diameter (mm)	2.40 ±0.10x2C
Color Code	Black, White

Outer Shield

Shield Type	Tape
Material	Al-PET Shield
Coverage	>=115%
Drain Wire Type	22 AWG Tinned Copper

Outer Jacket

Material	CMR - Polyvinyl Chloride
Nominal Thickness (mm)	0.43
Nominal Diameter (mm)	5.64±0.20
Rip Cord	Yes (Nylon-210D)

ELECTRICAL CHARACTERISTICS

Electrical

Max Con DC Resistance at 20°C(Ω/km)	<9.2
20°C Ins. Resistance (MΩ.KM)	>200
Nominal Conductor DCR	2.40 Ohm/305 m
Voltage	300V (CMR)

MECHANICAL CHARACTERISTICS

Temperature Range (°C)	-20°C to +75°C
Bend Radius (mm)	55.50
Max Pull Tension	47 kg
Bulk Cable Weight	17 kg/305 m

STANDARDS & COMPLIANCE

Environmental Suitability: Indoor-Riser, Indoor

Flammability /Reaction to Fire: UL 1666 Riser, FT4: IEC 60332-1-2

CPR Compliance: CPR Euroclass: Eca

NEC/UL Compliance

RoHS2(2011/65/EU Compliant)

UL Number E535337

Disclaimer

@2023 CHH Conex all rights reserved

All Rights Reserved. Although CHH make every reasonable effort to ensure their accuracy all the time of this publication information and specification prescribed herein are subject to error or omission to changes without notice and all listing or such information and specifications does not ensure product availability. (5100FE)