



Product Code: **C1318F**

Control, Security, Audio, BMS, 3 Conductor, 18 AWG, BC, PP Ins, PVC, CMR

Product Description

Multi-Conductor, Security, Audio, Control Cable, BMS, 3 Conductor, 18 AWG, Stranded Bare Copper Conductor, Polypropylene Insulation, Shielded, CMR Polyvinyl Chloride Jacket with 210D Nylon Rip Cord

TECHNICAL SPECIFICATION

Suitable Application Control, Audio, Data, Monitoring Building Management System.

Conductor

Element	Conductor(s)
No. of Element	3
Size	18 AWG
Stranding	7x26
Material	Bare Copper

Insulation

Material	PP - Polypropylene
Nominal Thickness (mm)	0.30
Nominal Diameter (mm)	1.80±0.10
Color Code	Black, Red, White

Outer Shield

Shield Type	Tape
Material	Al-Pet Shield
Coverage	>=115%
Drain Wire Type	24 AWG Tinned Copper

Outer Jacket

Material	CMR Polyvinyl Chloride
Nominal Thickness (mm)	0.60
Nominal Diameter (mm)	5.20±0.30
Rip Cord	Yes

ELECTRICAL CHARACTERISTICS

Electrical

Max Con DC Resistance at 20°C(Ω/km)	<21.3
20°C Ins. Resistance (MΩ.KM)	>200
Nominal Conductor DCR	6.50 Ohm/305 m
Voltage	300v (CMR)

MECHANICAL CHARACTERISTICS

Temperature Range (°C)	-20°C to +75°C
Bend Radius (mm)	0.43
Max Pull Tension	37 kg

STANDARDS & COMPLIANCE

Environmental Suitability: Indoor-Triser, Outdoor

Reaction to Fire UL 1666 Riser: IEC 60332-1-2

UL Compliance: CMR

RoHS2(2011/65/EU Compliant)

UL Number E535337

Disclaimer

@2023 CHH Conex all rights reserved

All Rights Reserved. Although CHH make every resonable effort to ensure their accuracy all the time of this publication information and specification prescribed herein are subject to error or omission to changes without notice and all listing or such information and specifications does not ensure product availability. (5301FE)