



**Product Code: C2216U**

Control, Security, Audio, BMS, 2 Conductor, 16 AWG, BC, PP Ins, LSZH, Eca

### Product Description

Multi-Conductor, Security, Audio, Control Cable, BMS, 2 Conductor, 16 AWG, Stranded Bare Copper Conductor, Polypropylene Insulation, Low Smoke Zero Halogen Jacket with 210D Nylon Rip Cord

### TECHNICAL SPECIFICATION

**Suitable Application** Control, Audio, Data, Monitoring Building Management System.

#### Conductor

Element	Conductor(s)
No. of Element	2
Size	16 AWG
Stranding	19x29
Material	Bare Copper

#### Insulation

Material	PP - Polypropylene
Nominal Thickness (mm)	0.20
Nominal Diameter (mm)	1.85±0.10x2C
Color Code	Black, Red

#### Outer Jacket

Material	Low Smoke Zero Halogen
Nominal Thickness (mm)	0.41
Nominal Diameter (mm)	4.57±0.20
Rip Cord	Yes (Nylon-210D)

#### MECHANICAL CHARACTERISTICS

Temperature Range (°C)	-20°C to +70°C
Bend Radius Min (mm)	46.0
Max Pull Tension	15 kg

### ELECTRICAL CHARACTERISTICS

#### Electrical

Max Con DC Resistance at 20°C(Ω/km)	<15.4
20°C Ins. Resistance(MΩ/KM)	>200
Nominal Conductor DCR	4.20 Ohm/305 m
Voltage	300V

### STANDARDS & COMPLIANCE

Environmental Suitability: Indoor-Euroclass Eca, Non-halogenated

Flammability/Reaction to Fire: IEC 60332-1-2

CPR Compliance: CPR Euroclass: Eca

ISO/IEC Compliance: IEC 61034-2-Smoke Density Min Transmittance = 60%

RoHS2(2011/65/EU Compliant)

UL Number E535337

#### Disclaimer

@2023 CHH Conex all rights reserved

All Rights Reserved. Although CHH make every reasonable effort to ensure their accuracy all the time of this publication information and specification prescribed herein are subject to error or omission to changes without notice and all listing or such information and specifications does not ensure product availability. (4200UE)