



## Product Code **C1212F**

Control, Security, Audio, BMS, 2 Conductor, 12 AWG, Shielded, PVC, CMR

### Product Description

Multi-Conductor, Security, Audio, Control Cable, BMS, 2 Conductor 12 AWG, stranded bare copper conductor Polypropylene insulation shielded-CMR Jacket with Rip Cord

### TECHNICAL SPECIFICATION

**Suitable Application** Control, Audio, Data, Monitoring Building Management System.

#### Conductor

Element	Conductor(s)
No. of Element	2
Size	12 AWG
Stranding	7x26
Material	Bare Copper

#### Insulation

Material	PP-Polypropylene
Nominal Thickness (mm)	0.28
Nominal Diameter (mm)	2.87±0.10
Color Code	Black, White

#### Outer Shield

Shield Type	Tape
Material	Al-PET Shield
Coverage	>=115%
Drain Wire Type	24 AWG Tinned Copper

#### Outer Jacket

Material	PVC
Nominal Thickness (mm)	0.43±0.10
Nominal Diameter (mm)	6.7±0.10
Rip Cord	Yes

### ELECTRICAL CHARACTERISTICS

#### Electrical

Max Con DC Resistance at 20°C(Ω/km)	<5.43
Nominal Conductor DCR	1.6 Ohm/305 m
Nominal Capacitance Con to Con	210 pF/m
Voltage	300V (CMR)

### MECHANICAL CHARACTERISTICS

Operating Temperature (°C)	-20°C to +75°C
Bend Radius (mm)	66.0
Max Pull Tension	163 lbs
Bulk Cable Weight	27 kg/305 m

### STANDARDS & COMPLIANCE

Environmental Suitability: Indoor-Riser, Indoor

Flammability/Reaction to Fire: UL 1666 Riser: IEC 60332-1-2

UL Compliance: CMR

RoHS2(2011/65/EU Compliant)

UL Number E535337

#### Disclaimer

@2023 CHH Conex all rights reserved

All Rights Reserved. Although CHH make every reasonable effort to ensure their accuracy all the time of this publication information and specification prescribed herein are subject to error or omission to changes without notice and all listing or such information and specifications does not ensure product availability.