



Complete Solutions designed to help connect your world for a smarter, Suitable future



Product Code **C1220F**

Control, Security, Audio, BMS, 2 Conductor, 20 AWG, Shielded, PVC, CMR

Product Description

Multi-Conductor, Security, Audio, Control Cable, BMS, 2 Conductor 20 AWG stranded bare copper conductor Polypropylene insulation shielded-CMR Jacket with Rip Cord

TECHNICAL SPECIFICATION

Suitable Application Control, Audio, Data, Monitoring Building Management System.

Conductor

Element	Conductor(s)
No. of Element	2
Size	20 AWG
Stranding	7x28
Material	Bare Copper

Insulation

Material	PP-Polypropylene
Nominal Thickness (mm)	0.20
Nominal Diameter (mm)	1.40±0.10
Color Code	Black, Red

Outer Shield

Shield Type	Tape
Material	Al-Foil Shield
Coverage	>=115%
Drain Wire Type	24 AWG Tinned Copper

Outer Jacket

Material	CMR PVC
Nominal Thickness (mm)	0.45
Nominal Diameter (mm)	3.70±0.30
Rip Cord	Yes

ELECTRICAL CHARACTERISTICS

Electrical

Max Con DC Resistance at 20°C(Ω/km)	<37.2
Nominal Conductor DCR	10.4 Ohm/305 m
Nominal Capacitance	130 pF/m
Voltage	300V (CMR)

MECHANICAL CHARACTERISTICS

Operating Temperature (°C)	-20°C to +75°C
Bend Radius (mm)	35.0
Max Pull Tension	14 kg
Bulk Cable Weight	7.0 kg/305 m

STANDARDS & COMPLIANCE

Environmental Suitability: Indoor-Riser, Indoor

Flammability/Reaction to Fire: UL 1666 Riser: IEC 60332-1-2, FT4

RoHS2(2011/65/EU Compliant)

UL Number E535337

Disclaimer

@2023 CHH Conex all rights reserved

All Rights Reserved. Although CHH make every reasonable effort to ensure their accuracy all the time of this publication information and specification prescribed herein are subject to error or omission to changes without notice and all listing or such information and specifications does not ensure product availability.



5400FE