



## Product Code: C1618U

Control, Security, Audio, BMS, 6 Conductor, 18 AWG, PVC, CMR

### Product Description

Multi-Conductor, Security, Audio, Control Cable, BMS, 6 Conductor, 18 AWG stranded bare copper conductor Polypropylene insulation, CMR Jacket with Rip Cord

### TECHNICAL SPECIFICATION

**Suitable Application** Control, Audio, Data, Monitoring Building Management System.

#### Conductor

Element	Conductor(s)
No. of Element	6
Size	18 AWG
Stranding	7x26
Material	Bare Copper

#### Insulation

Material	PP-Polypropylene
Nominal Thickness (mm)	0.23
Nominal Diameter (mm)	1.60±0.10
Color Code	Black, Red, White, Green, Blue, Brown

#### Outer Jacket

Material	CMR PVC
Nominal Thickness (mm)	0.43
Nominal Diameter (mm)	5.6±0.10
Rip Cord	Yes

### MECHANICAL CHARACTERISTICS

Operating Temperature (°C)	-20°C to +75°C
Bend Radius (mm)	56.0
Max Pull Tension	65.0 kg

### ELECTRICAL CHARACTERISTICS

#### Electrical

Max Con DC Resistance at 20°C(Ω/km)	<21.3
Nominal Conductor DCR	6.5 Ohm/305 m
Voltage	300V (CMR)

### STANDARDS & COMPLIANCE

Environmental Suitability: Indoor-Riser, Indoor

Flammability/Reaction to Fire: UL 1666 Riser: IEC 60332-1-2, FT4

CPR Compliance: CPR Euroclass: Eca

RoHS2(2011/65/EU Compliant)

UL Number E535337

#### Disclaimer

@2023 CHH Conex all rights reserved

All Rights Reserved. Although CHH make every reasonable effort to ensure their accuracy all the time of this publication information and specification prescribed herein are subject to error or omission to changes without notice and all listing or such information and specifications does not ensure product availability.