



## Product Code **KN00208**

EIB, 2 Pair, 4 Conductor, 0.8mm, Solid Bare Copper, PVC Insulation, OS, PVC Jacket, Eca

### Product Description

KNX/EIB, 2 Pair, 4 Conductor, 0.8mm, Solid Bare Copper, PVC Insulation, OS, PVC Jacket, Eca

### TECHNICAL SPECIFICATION

**Suitable Application** KNX/EIB cable for building management

#### Conductor

Conductor Count	4
Total Number of Pairs	2
Cross Section:	0.5 mm <sup>2</sup>
Stranding	Solid
Nominal Diameter (mm)	0.8
Material	Bare Copper

#### Outer Shield

Type	Tape
Material	BI-Laminate (Alum+Poly)
Coverage	100%
Drain Wire Material	TC- Tinned Copper
Drain Wire Diameter (mm)	0.4
Thickness of Foil	9 µm

#### Cabling

**Description** 1 Quad covered with Polyester Foil

#### Insulation

Material	PE - Polyethylene
Nominal Diameter (mm)	1.4±0.5
Nominal Wall Thickness (mm)	0.4

#### Outer Jacket

Material	PVC-Polyvinyl Chloride
Nominal Diameter (mm)	6.0
Diameter +/- Tolerance (mm)	0.3
Nominal Wall Thickness (mm)	1.2

#### Color Chart

Number	Quad 1
Colour	White & Red, Yellow & Black

### ELECTRICAL CHARACTERISTICS

#### Electrical

Max Con DCR	37.5 Ohm/km
Nominal Capacitance Con to Con	50 pF/m
Elec Characteristic Notes	Test Voltages 4 KV, 1 Min
Voltage Rating [V]	300V

### MECHANICAL CHARACTERISTICS

Temperature Range	-30°C to +70°C
Operating Temperature Range	-20°C to +70°C
Min Bend Radius During Installation (mm)	61
Min Setting Radius (mm)	30

### STANDARDS & COMPLIANCE


CPR Euroclass: Eca

IEC Flammability: IEC 60332-1-2

Environmental Space: Indoor Euroclass Eca

Update & Revision: Revision No. 4 12-06-2023

### CONSTRUCTION



#### Disclaimer

@2023 CHH Conex all rights reserved

All Rights Reserved. Although CHH make every reasonable effort to ensure their accuracy all the time of this publication information and specification prescribed herein are subject to error or omission to changes without notice and all listing or such information and specifications does not ensure product availability.

YE00820