



Product code **KN01108**

KNX/EIB, 1 Pair, 2 Conductor, 0.8mm, Solid Bare Copper, PE Insulation, OS, LSZH/FRNC Jacket, Eca

Product Description

KNX/EIB, 1 Pair, 2 Conductor, 0.8mm, Solid Bare Copper, PE Insulation, OS, LSZH/FRNC Jacket, Eca

TECHNICAL SPECIFICATION

Suitable Application KNX/EIB cable for building management

Conductor

Conductor Count	2
Total Number of Pairs	1
Cross Section:	0.5 mm ²
Stranding	Solid
Nominal Diameter (mm)	0.8
Material	Bare Copper

Insulation

Material	PE - Polyethylene
Nominal Diameter (mm)	1.6±0.05
Nominal Wall Thickness (mm)	0.4

Outer Shield

Type	Tape
Material	BI-Laminate (Alum+Poly)
Coverage	100%
Drain Wire Material	TC- Tinned Copper
Drain Wire Diameter (mm)	0.4
Thickness of Foil	9 µm

Outer Jacket

Material	LSZH- Low Smoke Zero Halogen
Nominal Diameter (mm)	6.0
Diameter +/- Tolerance (mm)	0.3
Nominal Wall Thickness (mm)	1.4

Cabling

Description 1 Pair covered with Polyester Foil

Color Chart

Number	Pair 1
Colour	Red & Blue

ELECTRICAL CHARACTERISTICS

Electrical

Max Con DCR	37.5 Ohm/km
Nominal Capacitance Con to Con	50 pF/m
Elec Characteristic Notes	Test Voltages 4 KV, 1 Min
Voltage Rating [V]	300V

MECHANICAL CHARACTERISTICS

Storage Temperature Range	-30°C to +70°C
Operating Temperature Ranges	-20°C to +70°C
Min Bend Radius During Installation (mm)	31.5
Min Setting Radius (mm)	63

STANDARDS & COMPLIANCE

CPR Euroclass: Eca

IEC Flammability: IEC 60332-1-2


IEC 60754-1- Halogen Amount - Zero

IEC 60754-2- Halogen Acid Gas Amount-Max Conductivity: 2.5 µS/mm

Environmental Space: Indoor Euroclass Eca

Update & Revision: Revision No. 4 12-06-2023

CONSTRUCTION



Disclaimer

@2023 CHH Conex all rights reserved

All Rights Reserved. Although CHH make every reasonable effort to ensure their accuracy all the time of this publication information and specification prescribed herein are subject to error or omission to changes without notice and all listing or such information and specifications does not ensure product availability.

YE00905