

**Product Code: LAS112**

Universal, 12 Fiber, Single Mode, Central Loose Tube, Corrugated Steel Tape, LSNH

**Product Description**

Universal, Fiber Optic Cable, Gel Filled, Loose Tube, Water Swellable Dry Material Core., Higher Level of Rodent Protection (Glass Yarn) Corrugated Steel Tape , Flame Retardant, Low Smoke Zero Halogen, Max-24 Fiber, Single Mode, 9/125, G652D G.657A1-OS2, CLT

**Suitable Application**

For outdoor and indoor use in structured (data) wiring systems such as industrial backbone building backbone (riser) and/or horizontal cabling. For outdoor and indoor use in networks for industrial, telecom, cable TV and/or broadcast. Easy to install in ducts, tunnels and trenches and/or tubes. Suitable for Direct Burial

**Mechanical and Environmental properties**

Test	Value	Unit	Method
Cable outer diameter	7,9 ± 0,4	mm	EN 60811-203
Cable weight	87	kg/km	
Outer Jacket Thickness	1,3	mm	
Loose Tube Diameter	3	mm	
Max. Tensile Strength	1100	N	EN6 0794-1-21-E1
Crush Resistance Test	3000	N	EN6 0794-1-21-E3
Impact Resistance Test	15	NM	EN6 0794-1-21-E4
Min. Bend Radius (no load)	15	x OD	EN 6 0794-1-21-E11a
Min Bend Radius (load)	20	x OD	EN 6 0794-1-21-E11b
Moisture resistance test	pass		EN 6 0794-1-22-F5
Temperature Range	Installation	-15 to +50	° C
	Operation	-20 to +70	° C
	Storage	-20 to +70	° C
CPR Fire Class	Dca- s2, d1, a1		
Fire Properties-Flammability	pass		EN 60332-3-22 (cat. A)
Fire Properties- Add Gases			EN 60754-1
	pass		EN 60754-2
Fire Properties- Smoke Density			EN 61034-1
	pass		EN 61034-2

Cable Life Time- minimum 30 years

**Sheat Marketing**

Print Colour	White
Print Method	Ink-jet
Print Legend	Manufacturer's name, job number, type of cable, length marking @ 1 m intervals

other print legends available on request

**Fiber Colour Coding**

According to IEC 60304


1 Red	7 Brown	13 Red*	19 Brown*
2 Green	8 Violet	14 Green*	20 Violet*
3 Blue	9 Turquoise	15 Blue*	21 Turquoise*
4 Yellow	10 Black	16 Yellow*	22 Black*
5 White	11 Orange	17 White*	23 Orange*
6 Grey	12 Pink	18 Grey*	24 Pink*

\* with block rings

Other future colour sequences available on request

**Packing**

Depending on ordered piu-up lengths



Black FR-LSZH outer jacket, UV dstable (colours available in request)  
Corrugated steel tape  
Gel filled loose tube with optical fibres  
waterblocking E-glass yarn



**Disclaimer**

@2023 CHH Conex. All right reserved.

All Rights Reserved. Although CHH makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications prescribed herein are subject to error or omission and to changes without notice and the listing of such information and specifications does not ensure product availability

GUCN812

