



Product Code: **LUS112**

Universal(Indoor - Outdoor), 12 Fiber, OS2, Single Mode, Central Loose Tube, Gel Filled, FR-LSZH outer Jacket

Product Description

Universal, Fiber Optic Cable, Gel Filled Loose Tube, Water Swellable Dry Material, Higher Level of Rodent Protection (Glass Yarn), Flame Retardant Low-Smoke Zero Halogen, Non-corrosive, UV Stable, 12 Fiber, Single mode 12x E9/125 G.657.A1, OS2, CPR Euroclass Dca

Suitable Application

Designed for data wiring systems in both indoor and outdoor settings, ideal for industrial backbone building, riser, and horizontal cabling. Suited for various networks including industrial, telecom, cable TV, and broadcast. Installation is hassle-free in, conduits, tubes, tunnels, ducts, and trenches

Mechanical and Environmental properties

| Test | Value | Unit | Method |
|-----------------------------------|--|------------|------------------------|
| Cable outer diameter | 5,8 ± 0,4 | mm | EN 60811-203 |
| Cable weight | 37 | kg/km | |
| Outer Jacket Thickness | 0,85 | mm | |
| Loose Tube Diameter | 3,2 | mm | |
| Max. Tensile Strength | 1100 | N | EN60794-1-21-E1 |
| Crush Resistance Test | 2000 | N | EN60794-1-21-E3 |
| Impact Resistance Test | 10 | NM | EN60794-1-21-E4 |
| Min. Bend Radius (no load) | 10 | x OD | EN 60794-1-21-E11a |
| Min Bend Radius (load) | 15 | x OD | EN 60794-1-21-E11b |
| Moisture resistance test | pass | | EN 60794-1-22-F5 |
| Temperature Range | Installation | -15 to +50 | °C |
| | Operation | -20 to +70 | °C |
| | Storage | -20 to +70 | °C |
| Fire Properties-Flammability | pass | | EN 60332-3-22 (cat. A) |
| Fire Properties- Add Gases | | | EN 60754-1 |
| | | | EN 60754-2 |
| Fire Properties- Smoke Density | | | EN 61034-1 |
| | | | EN 61034-2 |
| Cable Life Time- minimum 30 years | | | |
| Sheat Marketing | | | |
| Print Colour | White | | |
| Print Method | Ink-jet | | |
| Print Legend | CHH CONEX, job number, type of cable, length, Made in Czech Republic marking @ 1 m intervals | | |

other print legends available on request

Fiber Colour Coding


| | | | |
|----------|--------------|------------|---------------|
| 1 Red | 7 Brown | 13 Red* | 19 Brown* |
| 2 Nature | 8 Black | 14 Nature* | 20 Black* |
| 3 Yellow | 9 Orange | 15 Yellow* | 21 Orange* |
| 4 Blue | 10 Turquoise | 16 Blue* | 22 Turquoise* |
| 5 Green | 11 Pink | 17 Green* | 23 Pink* |
| 6 Violet | 12 White | 18 Violet* | 24 White* |

* with block rings

Other colour sequences available on request

Packing

Depending on ordered put-up lengths



GUSN812

Disclaimer

@2023 CHH Conex. All right reserved.

All Rights Reserved. Although CHH makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications prescribed herein are subject to error or omission and to changes without notice and the listing of such information and specifications does not ensure product availability

