



**Product Code: C2618F**

Control, Security, Audio, BMS, 6 Conductor, 18 AWG, BC-twisted, PP Ins, LSZH, Eca

**Product Description**

Multi-Conductor, Security, Audio, Control Cable, BMS, 6 Conductor, 18 AWG, Stranded Bare Copper-twisted Conductor, Polypropylene Insulation, Shielded, Low Smoke Zero Halogen Jacket with 210D Nylon Rip Cord

**TECHNICAL SPECIFICATION**

**Suitable Application** Control, Audio, Data, Monitoring Building Management System.

**Conductor**

Element	Conductor(s)
No. of Element	6
Size	18 AWG
Stranding	7x26
Material	Bare Copper

**Insulation**

Material	PP - Polypropylene
Nominal Thickness (mm)	0.20
Nominal Diameter (mm)	1.60±0.10x6C
Color Code	Black, Red, White, Green, Brown, Blue

**Outer Shield**

Shield Type	Tape
Material	Al-PET Shield
Coverage	>=115%
Drain Wire Type	24 AWG Tinned Copper

**Outer Jacket**

Material	Low Smoke Zero Halogen
Nominal Thickness (mm)	0.40
Nominal Diameter (mm)	5.70±0.20
Rip Cord	Yes (Nylon-210D)

**ELECTRICAL CHARACTERISTICS**

**Electrical**

Max Con DC Resistance at 20°C(Ω/km)	<21.60
20°C Ins. Resistance (MΩ.KM)	>200
Voltage	300V

**MECHANICAL CHARACTERISTICS**

Operating Temperature (°C)	-20°C to +70°C
Bend Radius (mm)	57.0
Max Pull Tension	21.5 kg

**STANDARDS & COMPLIANCE**

Environmental Suitability: Indoor-Riser, Indoor

Rection to Fire: IEC 60332-1-2

UL Compliance: CM

RoHS2(2011/65/EU Compliant)

UL Number E535337

**Disclaimer**

@2023 CHH Conex all rights reserved

All Rights Reserved. Although CHH make every resonable effort to ensure their accuracy all the time of this publication information and specification prescribed herein are subject to error or omission to changes without notice and all listing or such information and specifications does not ensure product availability. (4304FE)