



Product Code: C2618U-3P

Control, Security, Audio, BMS, 3 Pairs, 18 AWG, BC-twisted, PE Ins, LSZH, Eca

Product Description

Multi-Conductor, Security, Audio, Control Cable, BMS, 3 Pairs, 18 AWG, Stranded Bare Copper-twisted, Polyethylene Insulation, Unshielded, Low Smoke Zero Halogen Jacket with 210D Nylon Rip Cord

TECHNICAL SPECIFICATION

Suitable Application Control, Audio, Data, Monitoring Building Management System.

Conductor

Element	Pair(s)
No. of Element	3
Size	18 AWG
Stranding	7x26
Material	Bare Copper

Insulation

Material	PE - Polyethylene
Nominal Thickness (mm)	0.20
Nominal Diameter (mm)	1.60±0.1x2C - Twistx3
Color Code	Black/Red, Black/White, Black/Green

Outer Jacket

Material	Low Smoke Zero Halogen
Nominal Thickness (mm)	0.40
Nominal Diameter (mm)	6.70±0.30
Rip Cord	Yes (Nylon-210D)

MECHANICAL CHARACTERISTICS

Operating Temperature (°C)	-20°C to +70°C
Bend Radius (mm)	68.2
Max Pull Tension	32.6 kg

ELECTRICAL CHARACTERISTICS

Electrical

Max Con DC Resistance at 20°C(Ω/km)	<21.60
20°C Ins. Resistance (MΩ.KM)	>200
Voltage	300V

STANDARDS & COMPLIANCE

Environmental Suitability: Indoor-Riser, Indoor

Reaction to Fire: IEC 60332-1-2

UL Compliance: CM

RoHS2(2011/65/EU Compliant)

UL Number E535337

Disclaimer

@2023 CHH Conex all rights reserved

All Rights Reserved. Although CHH make every reasonable effort to ensure their accuracy all the time of this publication information and specification prescribed herein are subject to error or omission to changes without notice and all listing or such information and specifications does not ensure product availability. (4342UE)

